

## LED CordLights™

Engineered Products Company's (EPCO) LED CordLights are an energy efficient, labor saving alternative to traditional string lights. Constructed of heavy-duty 18/2 or 18/3 SJTW round cord and available in 50- or 100-foot lengths, these CordLights are ETL Listed, comply with UL Standard 153 for Portable Electric Luminaires, and are suitable for a variety of temporary construction lighting applications.

### BENEFITS

- Each LED Module produces excellent 5000K white light.
- Labor savings! Easy installation and no lamps to replace.
- Reduced energy costs with minimal power draw.
- Tested for optimal performance, durability, and reliability.
- Suitable for damp and wet locations.
- IP65 Weather-resistant LED Modules resist dust and rain.
- Meets the requirements of the 2023 National Electrical Code: Articles 590.4(E)(F)(J)
- Beam Angle: 120°.
- Linkable to connect additional LED CordLights.

### FEATURES

- Commercial grade, high-power LEDs.
- Available in 50- or 100-foot lengths.
- 10-Foot spacing between LED Modules.
- Constructed of heavy duty 18/2 or 18/3 SJTW round cord.
- 120-Volt plug and receptacle.
- Includes carabiner coupling link to expedite installation.

### Typical Lighting Applications

- Construction and Renovation Job Sites
- Parking Lots
- Walkways
- Festivals
- Special Events
- Christmas Tree Lots
- Outdoor Markets
- Emergency Lighting
- Small Warehouse Working Spaces

### Magnetic Suspension Hangers for LED CordLights

EPCO's Magnetic Suspension Hangers are the strongest "commercial grade" magnets for suspending all EPCO LED CordLight Luminaires.

- Maximum holding force - 22 lbs.
- Improves installation and tear down for labor savings.



Magnetic Suspension Hangers  
for LED CordLight  
Part Number: CORDLIGHT-MH



LED CordLights  
(Standard Lumen Output, 1,500 Lumens per Module)  
Part Number: 16145



LED CordLights  
(Standard Lumen Output, 1,600 Lumens per Module)  
Part Number: 16140 and 16143



LED CordLights  
(High Lumen Output, 2,000 Lumens per Module)  
Part Number: 16050



Typical Application: EPCO's LED CordLights illuminating a construction site after the exterior has been enclosed.

## LED CordLights Specifications

	Part Number: 16140	Part Number: 16143	Part Number: 16145	Part Number: 16050
Output Lumens	16,000 (1,600 per LED Light Module)	16,000 (1,600 per LED Light Module)	7,500 (1,500 per LED Light Module)	20,000 (2,000 per LED Light Module)
Operating Voltage	120 VAC	120 VAC	120 VAC	120 VAC
Watts	130-Watts	130-Watts	60-Watts	160-Watts
Correlated Color Temperature (CCT)	5000K	5000K	5000K	5000K
Color Rendering Index (CRI)	≥80	≥80	≥80	≥80
Efficacy	125 lm/W	25 lm/W	125 lm/W	125 lm/W
Operating Temperature	-4°F (-20°C) to 104°F (40°C)	-4°F (-20°C) to 104°F (40°C)	-4°F (-20°C) to 104°F (40°C)	-4°F (-20°C) to 104°F (40°C)
Applications	Damp or Wet Locations	Damp or Wet Locations	Damp or Wet Locations	Damp or Wet Locations
Certifications	<ul style="list-style-type: none"> <li>■ ETL Listed</li> <li>■ IP65 Rated</li> </ul>	<ul style="list-style-type: none"> <li>■ ETL Listed</li> <li>■ IP65 Rated</li> </ul>	<ul style="list-style-type: none"> <li>■ ETL Listed</li> <li>■ IP65 Rated</li> </ul>	<ul style="list-style-type: none"> <li>■ ETL Listed</li> <li>■ IP65 Rated</li> </ul>
Power Cord Type	<ul style="list-style-type: none"> <li>■ 18/2 Heavy Duty SJTW Cord</li> <li>■ 120V, 1-15 Plug &amp; Receptacle</li> </ul>	<ul style="list-style-type: none"> <li>■ 18/3 Heavy Duty SJTW Cord</li> <li>■ 120V, 5-15 Plug &amp; Receptacle</li> </ul>	<ul style="list-style-type: none"> <li>■ 18/2 Heavy Duty SJTW Cord</li> <li>■ 120V, 1-15 Plug &amp; Receptacle</li> </ul>	<ul style="list-style-type: none"> <li>■ 18/2 Heavy Duty SJTW Cord</li> <li>■ 120V, 1-15 Plug &amp; Receptacle</li> </ul>
LED Module/Power Cord Color	Black/Yellow	Black/Yellow	Black/Yellow	Black/Yellow
Warranty	3-Year	3-Year	3-Year	3-Year
Linkable Maximum	Four (4) Maximum	Four (4) Maximum	Eight (8) Maximum	Three (3) Maximum

**Note:** Replacement Fuse — Bussmann Series, Product Code GMA-8-R

## PART NUMBERS

Catalog Number	UPC Number	Description	Order Unit	Unit Qty	Unit Pkg	Units/Case	TL Case Qty	Min Order Qty	MM Req	Ship Wt (Lbs)
16140	16140	LED CordLights: 100-FT Length, 18/2, Standard Output	EA	1	BX	2	2	1	No	9
16143	16143	LED CordLights: 100-FT Length, 18/3, Standard Output	EA	1	BX	2	2	1	No	9
16145	16145	LED CordLights: 50-FT Length, Standard Output	EA	1	BX	4	4	1	No	5
16050	16050	LED CordLights: 100-FT Length, High Output	EA	1	BX	2	2	1	No	11
CordLight-MH	16049	Magnetic Suspension Hanger: For LED CordLights	EA	1	BG	1	1	1	No	≤1

16140 and 16145



16145



16050



### UNITS OF MEASURE KEY

**Order Unit:** The Unit to be ordered; **Order Qty:** Number of pieces in each Unit; **Unit Pkg:** Packaging types - BG (Bag), BX (Box), BRL (Barrel); **Units/Case:** Unit packages contained in the Case; **TL Case Qty:** The total number of items in each Master Case; **Min Order Qty:** The smallest Unit that can be ordered; **MM Req:** Must order multiples of the Unit in the stated quantities; **Ship Wt (Lbs):** Total weight of the units per Carton

E02-150-042 (12/24 AK)  
©2024 Engineered Products Company. All Rights Reserved.

